

Lexmark MS811 (Page 1)

Paper Menu

Default Source = Tray 1
Paper Size/Type
Tray 1 Size = Letter
Tray 1 Type = Plain Paper
Tray 2 Size = Legal
Tray 2 Type = Custom Type 2
MP Feeder Size = Legal
MP Feeder Type = Custom Type 6
Manual Paper Size = Letter
Manual Paper Type = Plain Paper
Manual Envelope Size = 10 Envelope
Manual Envelope Type = Envelope
Configure MP = Cassette
Substitute Size = All Listed

Paper Texture

Plain Texture = Normal
Card Stock Texture = Normal
Transparency Texture = Normal
Recycled Texture = Normal
Labels Texture = Normal
Vinyl Labels Texture = Normal
Bond Texture = Rough
Envelope Texture = Normal
Rough Envelope Texture = Rough
Letterhead Texture = Normal
Preprinted Texture = Normal
Colored Texture = Normal
Light Texture = Normal
Heavy Texture = Normal
Rough/Cotton Texture = Rough
Custom 1 Texture = Normal
Custom 2 Texture = Normal
Custom 3 Texture = Normal
Custom 4 Texture = Normal
Custom 5 Texture = Normal
Custom 6 Texture = Normal

Paper Weight

Plain Weight = Normal
Card Stock Weight = Normal
Transparency Weight = Normal
Recycled Weight = Normal
Labels Weight = Normal
Vinyl Labels Weight = Normal
Bond Weight = Normal
Envelope Weight = Normal
Rough Envelope Weight = Heavy
Letterhead Weight = Normal
Preprinted Weight = Normal
Colored Weight = Normal
Light Weight = Light
Heavy Weight = Heavy
Rough/Cotton Weight = Normal
Custom 1 Weight = Normal
Custom 2 Weight = Normal
Custom 3 Weight = Normal
Custom 4 Weight = Normal
Custom 5 Weight = Normal
Custom 6 Weight = Normal

Custom Types

Custom Type 1 = Paper
Custom Type 2 = Paper
Custom Type 3 = Paper
Custom Type 4 = Paper
Custom Type 5 = Paper
Custom Type 6 = Paper
Recycled = Paper

Universal Setup

Units of Measure = Inches
Portrait Width = 8.50inches
Portrait Height = 14.00inches

Reports

Menu Settings Page
Device Statistics
Network Setup Page
Print Fonts
PCL Fonts
PostScript Fonts
Print Demo
Asset Report
Event Log Summary

Network/Ports

Active NIC = Auto

Standard Network

Std Network Setup

Reports

Print Setup Page

Network Card

View Card Status = Not Connected
View Card Speed = Unknown
Energy Efficient Ethernet = On

Network Address

UAA = 0021B7E90AD8
LAA = 000000000000
End-of-Job Timeout = 90
Banner Page = Off

TCP/IP

Set Hostname = P-375798
IP Address = 172.25.133.253
Netmask = 255.255.254.0
Gateway = 172.25.132.1
Enable DHCP = On
Enable AutoIP = Yes
Enable FTP/TFTP = Yes
Enable HTTP Server = Yes
WINS Server Address = 199.215.68.9
Enable DDNS = Yes
Enable mDNS = Yes
DNS Server Address = 199.215.64.34
Backup DNS Server Address = 199.213.24.34
Backup DNS Server Address 2 = 199.215.83.159
Backup DNS Server Address 3 = 199.213.24.33
Enable HTTPS = Yes

IPv6

Enable IPv6 = Off
Auto Configuration = Off
View Hostname = P-375798
View Address = fe80::221:b7ff:f...
View Router Address = ::
Enable DHCPv6 = Off

PCL SmartSwitch = On
PS SmartSwitch = On
NPA Mode = Auto
Network Buffer = Auto
Mac Binary PS = Auto

Standard USB

PCL SmartSwitch = On
PS SmartSwitch = On
NPA Mode = Auto
USB Buffer = Auto
Mac Binary PS = Auto

Lexmark MS811 (Page 2)

Network/Ports(Cont.)

SMTP Setup

Primary SMTP Gateway	=
Primary SMTP Gateway Port	= 25
Secondary SMTP Gateway	=
Secondary SMTP Gateway Port	= 25
SMTP Timeout	= 30
Reply Address	=
Use SSL	= Disabled
SMTP Server Authentication	= No authentication re...
Device-Initiated E-mail	= None
Device Userid	=

Security

Confidential Print

Max Invalid PIN	= Off
Confidential Job Expiration	= Off
Repeat Job Expiration	= Off
Verify Job Expiration	= Off
Reserve Job Expiration	= Off

Security Audit Log

Export Log	
Delete Log	
Configure Log	
Enable Audit	= 2=No
Enable Remote Syslog	= 2=No
Remote Syslog Facility	= 4 - security
Severity of events to log	= 4 - Warning

Set Date and Time

Current Date and Time	= 2007-03-24 00:56
Manually Set Date & Time	= 1014432838
Time Zone	= (UTC-07:00) Mountain...
Automatically Observe DST	= On
Enable NTP	= Off

Settings

General Settings

Display Language	= English
Show Supply Estimates	= Show estimates
Eco-Mode	= Off
Quiet Mode	= Off
Safe Mode	= Off
Run initial setup	= No
Paper Sizes	= U.S.

Home screen customization

Change language	= Do not display
Search Held Jobs	= Display
Held Jobs	= Display
USB Drive	= Display
Bookmarks	= Do not display
Jobs by user	= Do not display

Output Lighting

Normal/Standby Mode	= Bright
---------------------	----------

Alarms

Alarm Control	= Single
Cartridge Alarm	= Off

Timeouts

Sleep Mode	= 20
Print with Display Off	= Display on when pr...
Hibernate Timeout	= 3 days
Screen Timeout	= 30
Print Timeout	= 90
Wait Timeout	= 40

Error Recovery

Auto Reboot	= Reboot always
Max Auto Reboots	= 2

Settings(Cont.)

Print Recovery

Auto Continue	= Disabled
Jam Recovery	= Auto
Jam Assist	= On
Page Protect	= Off
Hibernate Timeout on Con...	= Do Not Hibernate
Press Sleep Button	= Sleep
Press and Hold Sleep Button	= Do Nothing
Factory Defaults	= Do Not Restore
Custom Home Message	= Off

Flash Drive Menu

Print Settings

Copies	= 1
Paper Source	= Tray 1
Collate	= (1,2,3) (1,2,3)
Paper Saver Orientation	= Auto
Paper Saver	= Off
Paper Saver Border	= None
Paper Saver Ordering	= Horizontal
Separator Sheets	= Off
Separator Sheet Source	= Tray 1
Blank Pages	= Do Not Print

Print Settings

Setup Menu	
Printer Language	= PCL Emulation
Print Area	= Normal
Resource Save	= Off

Finishing Menu

Copies	= 1
Blank Pages	= Do Not Print
Collate	= (1,1,1) (2,2,2)
Separator Sheets	= Off
Separator Source	= Tray 1
Paper Saver	= Off
Paper Saver Ordering	= Horizontal
Paper Saver Orientation	= Auto
Paper Saver Border	= None

Quality Menu

Print Resolution	= 600 dpi
Pixel Boost	= Off
Toner Darkness	= 8 -.....v...+
Enhance Fine Lines	= Off
Gray Correction	= Auto
Brightness	= 0
Contrast	= 0

Utilities Menu

Activate Hex Trace	
Coverage Estimator	= Off

XPS Menu

Print Error Pages	= Off
-------------------	-------

PDF Menu

Scale To Fit	= No
Annotations	= Do Not Print

PostScript Menu

Print PS Error	= Off
Lock PS Startup Mode	= Off

PCL Emul Menu

Font Source	= Resident
Font Name	= R0 Courier
Symbol Set	= 10U PC-8

PCL Emulation Settings

Pitch	= 10.00
Orientation	= Portrait
Lines per Page	= 60
A4 Width	= 198 mm
Auto CR after LF	= Off
Auto LF after CR	= Off

Lexmark MS811 (Page 3)

Settings(Cont.)

Tray Renumber
Assign MP Feeder = Off
Assign Tray 1 = Off
Assign Tray 2 = Off
Assign Manual Paper = Off
Assign Manual Envelope = Off

View Factory Defaults

MPF Default = 8
T1 Default = 1
T2 Default = 4
T3 Default = 5
T4 Default = 20
T5 Default = 21
Env Default = 6
MPaper Default = 2
MEnv Default = 3

Restore Defaults

HTML Menu

Font Name = Times
Font Size = 12pt
Scale = 100%
Orientation = Portrait
Margin Size = 19mm
Backgrounds = Print

Image Menu

Auto Fit = On
Invert = Off
Scaling = Best Fit
Orientation = Portrait

Help

Print All Guides
Print Quality
Printing Guide
Media Guide
Print Defects Guide
Menu Map
Information Guide
Connection Guide
Moving Guide
Supplies Guide

Other Settings

Tray 1 Auto Size = Auto
Tray 2 Auto Size = Auto
Resolution Reduction = On
PCL Type 1 Fonts = On
Job Timeout = Disabled
Feed Timeout = 60
Stored Job Limit = 5
Tray Linking = On

Warnings

Invalid Factory Configuration

Device Information

Page Count = 16882
Installed Memory = 512 MB
Processor Speed = 800 MHz (2)
Processor ID = aaeb9410a29d0278
Serial Number = 40635C6600TRW
TLI = 40G0210
Engine Mode = 0
Machine Type = 4063-430
Asset Tag = P-375798
Hard Disk Last Erased =
Printer Memory Last Erased =
CalStat = 000f2eff
Engine ID = 55
Fuser Type = 00
Loader = LW40.DN2.P439-0
Kernel = FW4.YS.F439-0
Base = LW40.DN2.P439-0
Network = NH.YS.N439-0
Network Drvr = LW40.DN2.P439-0
Engine = FDN.DN.E609-0
Panel = v2.3e3.3hw5c129
Green Micro = Boot_v00.00-App_v01.12
Font = 8.11H01-U5.021
Tray 2 = A14.24_B1.10
SID =

Cartridge Information

Toner Level 
Serial Number = CAB173061F4D
Genuine
Capacity = 25.0K
Return
Type = Normal

Imaging Unit Information

Supply Status 
Serial Number = CAB192543C81
Genuine
Capacity = 100.0K
Type = Normal Return

Maintenance Kit Information

Supply Status = OK
Serial Number = 001502610730
Genuine
Capacity = 200.0K

Installed Features

550-Sheet Drawer

Asset Report (Page 1)

Device Information

Model Name Lexmark MS811
Asset Tag P-375798
Serial Number 40635C6600TRW
Mono Print Counts 16876
SID

Network Information

DNS Name 199.215.64.34
IP Address 172.25.133.253
MAC Address 0021B7E90AD8
Time 2007-03-24 00:59

Firmware Levels

Engine FDN.DN.E609-0
Loader LW40.DN2.P439-0
Kernel FW4.YS.F439-0
Base LW40.DN2.P439-0
Network NH.YS.N439-0
Network Drvr LW40.DN2.P439-0
Panel v2.3e3.3hw5c129
Font 8.11H01-U5.021